


Machinery Jack

Professional class
Conforms to CE safety standard.
TB100




Static loading capacity on top 10 tonne

| Model | Lifting Capacity | | Lifting Stroke | Lifting Range of Top | Min. Loading Height Using Lifting Toe | Min. Loading Height Using Lifting Toe at Max. Adjustment | Lifting Range of toe | Net Weight | Minimum Qty. |
|-------|------------------|---------|----------------|----------------------|---------------------------------------|--|----------------------|------------|--------------|
| | on top | on toe | | | | | | | |
| TB100 | 7.5 tonne | 6 tonne | 160 mm | 320-560 mm | 35 mm | 160 mm | 35-195 mm | 25 kg | 20 pcs |

Machinery Jack

Professional class
TB200



Static loading capacity on top 20 tonne

| Model | Capacity on Top | Capacity on Toe | Lifting Stroke | Lifting Range of Top | Min. Loading Height Using Lifting Toe | Min. Loading Height Using Lifting Toe at Max. Adjustment | Adjustable Range of the Lifting Toe | Lifting Range of toe | Net Weight | Minimum Qty. |
|-------|-----------------|-----------------|----------------|----------------------|---------------------------------------|--|-------------------------------------|----------------------|------------|--------------|
| TB200 | 15 tonne | 12 tonne | 140 mm | 325-545 mm | 40 mm | 140 mm | 2 X | 40-260 mm | 68 kg | 5 pcs |