

Model	EG3040 (48V)	
Descriptions:	HUNTING BUGGY	
General Specifications:		
Passenger capacity	4	
Voltage (V)	48V	
Range (loaded) (km)	80	
Max. speed (km/h)	33	
Max. climbing ability (loaded)	28%	
Overall dimensions(L*W*H)(mm)	2500x1200x1900	
Max. loading weight	380Kgs	
Net weight	480kgs	
Qty/40'	8PCS	
Qty/40'HQ	16pcs	
Configurations: ("S" stands for Standard configuration and "O" stands for Optional configuration)		
PART DESCRIPTIONS	REMARKS	
Body	Steel framework + fiberglass body	S
Body color	solid color	S
	camouflaged	O
Roof	fiberglass	S
Roof color	solid color	S
Windshield	one-piece see-through	S
	Foldable	O
Seats:		
1) backrest and cushion	Sponge + artificial leather	S
2) armrest	plastic	S
3) rear foldable seat	aluminum rear board	S
Floor	Non-slipping plastic	S
Protective side	stainless steel	S
front basket and top basket	/	S
Lighting system	front headlights, taillights(combined brake lights with reverse lights), with DC-DC converter (converting from 48V to 12V)	S
Horn	/	S
Dashboard	fiberglass	S
	1 battery charging meter,combined switch, key ignition, forward/reverse switch, horn switch	S
Battery	Trojan battery T605 X 8pcs	S
Motor	4KW	S
Controller	Curtis brand	S
Steering system	Single-stage rack and pinion steering system, automatic rocker compensating function	S
Brake system	mechanical brake + parking brake system	S
Accelerator	Stepless speed change	S
Suspension system	integrative front axle, leaf spring+vibration absorber	S
Driving mode	Rear axle two stage deceleration, motor direct driving	S
Rear axle	integrative rear axle, leaf spring + vibration absorber	S
Wheel and tyre	25 x 10-12 tyre	S
	22 x 10-10 tyre	O
hand bar	/	S
rear view mirror	external	O
	inner	O

ACCESSORIES:

Charger	China origin, input 110V-240V~50Hz-60Hz, output48V, 25A	S
1pc density checker for battery	\	S

Model	EG3040 (48V)	
Descriptions:	HUNTING BUGGY WITH UTILITY BOX	
General Specifications:		
Passenger capacity	4	
Voltage (V)	48V	
Range (loaded) (km)	80	
Max. speed (km/h)	33	
Max. climbing ability (loaded)	28%	
Overall dimensions(L*W*H)(mm)	2500x1200x1900	
Rear aluminum box (mm)	1100x800x250	
Max. loading weight	380Kgs	
Net weight	480kgs	
Qty/40'	8PCS	
Qty/40'HQ	16pcs	

Configurations: ("S" stands for Standard configuration and "O" stands for Optional configuration)

PART DESCRIPTIONS	REMARKS	
Body	Steel framework + fiberglass body	S
Body color	solid color	S
	camouflaged	O
Roof	fiberglass	S
Roof color	solid color	S
Windshield	one-piece see-through	S
	Foldable	O
Seats:		
1) backrest and cushion	Sponge + artificial leather	S
2) armrest	plastic	S
3) rear foldable seat	aluminum rear board	S
Floor	Non-slipping plastic	S
Protective side	stainless steel	S
front basket and front bumper	/	O
Lighting system	front headlights, taillights(combined brake lights with reverse lights), with DC-DC converter (converting from 48V to 12V)	S
Horn	/	S
Dashboard	fiberglass	S
	1 battery charging meter, combined switch, key ignition, forward/reverse switch, horn switch	S
Battery	Trojan battery T605 X 8pcs	S
Motor	4KW	S
Controller	Curtis brand	S
Steering system	Single-stage rack and pinion steering system, automatic rocker compensating function	S
Brake system	mechanical brake + parking brake system	S
Accelerator	Stepless speed change	S
Suspension system	integrative front axle, leaf spring+vibration absorber	S
Driving mode	Rear axle two stage deceleration, motor direct driving	S
Rear axle	integrative rear axle, leaf spring + vibration absorber	S
Wheel and tyre	25 x 10-12 tyre	S
	22 x 10-10 tyre	O
hand bar	/	S
rear view mirror	external	O
	inner	O

ACCESSORIES:

Charger	China origin, input 110V-240V~50Hz-60Hz, output48V, 25A	S
1pc density checker for battery	\	S