


Model name	LT-1916DT
IMAGE	
Specification:	
Panel	
Manufacturer	CMO/SVA
Size (")	19
Display Ratio	16:10
Resolution (Maximum Mode)/Frequency (Hz)	1440x900
Dot Pitch (Hmm x Vmm)	0.285x0.285
Viewing Angle (H/V)	170x160
Response Time (ms)	8
Brightness (Cd/m ²)	300
Contrast ratio	700:1
Display Color (millions)	16.2
Inputs	
Composite-Video input	1
S-Video input	-
Scart (RGB)	1
Component input (Y/Pb/Pr)	1
VGA	1
Audio input	1
RF input (75 ohm IEC-type)	1
USB	1
HDMI	1
PC Digital Input	-
PC Analog Input	-
RS-232C	-
PC Audio Stereo Input	1
Mic input	2
Outputs	
Composite-Video output	-
Audio output	-
Headphone Jack	1
SCART	1
Optical Digital Audio Output	-
Coaxial Digital Audio Output	1
TV tuner	
Colour System	PAL/SECAM
Tuners Quantity	1
Channel Quantity	100
NICAM decoder	1
Teletext (page qnt.)	-
DVB tuner	
DVB tuner	yes
Common Interface slot	Optional

Channel Quantity	-
Card Reader	
Card Reader	Optional
Design	-
Flash memory card types	-
DVD player	
DVD player	1
Disc loading mechanism	Slot-in
Formats	DVD/CD/VCD/MP3/DVD+R/DVD-R/JPG
Disc types	CD,DVD,CD-R/RW, DVD-R/RW, DVD+R/RW
Karaoke mix	yes
Features	
HDTV support	-
3-D video de-interlacer	yes
APE-Automatic Picture Enhancement	yes
2D Comb filter	1
3D Comb filter	-
Noise reduction	yes
On / Off Timer	-
Signal mode detection	-
PIP/POP	-
Languages	English/Others
Stand	kickstand
VESA wall mounting	1
Certification	CE
Speakers	
Type (detachable/undetachable)	built-in
Output Power RMS	3Wx2
Stereo Mode	1
Surround Modes	-
BBE ViVa	-
Power supply	
Voltage and frequency (V, Hz)	100~240(50/60)
Voltage of external EPU (V, A)	12V 4.5A
Power Consumption (Maximum) (W)	≤54
Power Consumption (Power Saving) (W)	≤3
Color	
Black	+
Dark Blue	
Silvery	+
White	
Others	
Operating temperature (oC)	5℃~35℃
Operating humidity (%)	85%
Storing temperature (oC)	0℃~50℃
Storing humidity (%)	85%
Dimensions (mm)(Net)	
Weight (kg)(without wall mounting)	
Package dimensions (mm)	
Package weight (kg)(without wall mounting)	

EAN	yes
-----	-----