

PVC Insulated material

Style UL1015 Hook-up Wire

Internal wiring of Appliances; or where exposed to oil at a temperature not exceeding 105°C
Whichever is applicable, The most popular hookup wire for Electric.

Description:

Conductor material of tinned or bare copper

Rated temperature 105 °C

Rated Voltage 600 V (Spark voltage 6000 V)

Flame resistance VW-1 and FT1

RoHS Compliant

Specification:

Gauge (AWG)	Number of Strands	Gauge of Strands (AWG)	Nom. Dia. of Stranded Conductor		Nom. Fin. Wire Diam.		Max. Resistance (dc at 20°C) Ohm/per		Nom. Wt.	
			Inch	mm	Inch	mm	1000-ft	Km	LBS./1000 ft.	Kg/Km
4/0	259	21	.5197	13.20	.6772	17.20	0.0525	0.1722	714.30	1062.74
3/0	259	22	.4610	11.71	.6185	15.71	0.0669	0.2194	573.21	852.83
2/0	259	23	.4173	10.60	.5748	14.60	0.0814	0.2670	477.77	710.83
1/0	259	24	.3657	9.29	.5232	13.29	0.1026	0.3367	377.53	561.68
1	259	25	.3331	8.46	.4906	12.46	0.1300	0.4268	319.52	475.38
2	259	26	.2854	7.25	.4051	10.29	0.1641	0.5384	228.42	339.85
4	133	25	.2386	6.06	.3583	9.10	0.2608	0.8559	166.50	247.71
6	266	30	.1882	4.78	.3079	7.82	0.4148	1.361	111.20	165.45
8	168	30	.1496	3.80	.2402	6.10	0.6795	2.23	69.13	102.85
10	105	30	.1181	3.00	.1811	4.60	1.08	3.55	41.71	61.89
12	65	30	.0933	2.37	.1563	3.97	1.72	5.64	27.85	41.33
14	41	30	.0740	1.88	.1370	3.48	2.73	8.96	19.25	28.58
16	26	30	.0591	1.50	.1220	3.10	4.45	14.6	13.71	20.34
18	1	18	.0402	1.02	.1031	2.62	6.77	22.2	9.48	14.07
18	16	30	.0465	1.18	.1094	2.78	7.06	23.2	9.84	14.60
20	1	20	.0320	0.813	.0950	2.41	10.7	35.2	7.16	10.63
20	21	33	.0374	0.95	.1004	2.55	11.2	36.7	7.61	11.27
22	17	34	.0299	0.76	.0929	2.36	18.1	59.4	5.95	8.84
24	11	34	.0240	0.61	.0870	2.21	28.7	94.2	4.84	7.20
26	7	34	.0197	0.50	.0827	2.10	45.8	150	4.09	6.07
28	1	28	.0126	0.32	.0756	1.92	69.3	227	3.27	4.86
28	7	36	.0154	0.39	.0783	1.99	72.8	239	3.49	5.19
30	1	30	.0100	0.254	.0730	1.85	110	361	2.92	4.35

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4 – Green W/ Yellow

Stripping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available