


CT250KD-3	Specifications	
	ENGINE	
	Displacement (cm ³)	249.4
	Cooling Mode	Water-cooled
	Bore x Stroke(mm)	71*63
	Compression Ratio	10.5 : 1
	Standard Power(KW/R/Min)	13.2/7000
	Maximum Torque(N.m/r/min)	20.6/5500
	Carburetion	PZ30M
	Ignition Type	CDI
	Start Mode	Electric
	Transmission	CVT
	Drive Train	Chain
	CHASSIS	
	Frame Mode	Pipe Board Mode
	Tire Size(Front)	23 x 7-10
Tire Size(Rear)	25 x 10-12	
Brake(Front)	Disc	
Brake(Rear)	Disc	
DIMENSIONS		
Dim(LxWxH)(mm)	2340 x 1620 x 1590	
Certificate	Dead Weight(kg)	330
EEC NO	Max.Weight(kg)	490
EPA NO	Wheel Base(mm)	1760
CARB NO	Ground Clearance(mm)	205
	Turning Radius(mm)	3930
	Fuel tank Capacity(L)	15
	Loading Quantity	20'GP/8pcs; 40'HQ/27pcs
Optional	OTHER	

	Max.Speed(km/h)	63
	Battery(V.Ah)	YTX12-BS
	Headlight	12V/35W x 2
	Brake Light/Taillight	12V/21W/5W