



 <b>MODEL</b> 555					
Model	Collocate Explain				
WP-505A2	Sony 1/3" 3.6mm Lens (6mm)				
WP-505B2	Sony 1/4" 3.6mm Lens (6mm)				
WP-505C2	Sharp 1/3" 3.6mm Lens (6mm)				
WP-505D2	Sharp 1/4" 3.6mm Lens (6mm)				
/Pickup Device	SHARP 1/3" CCD	SHARP 1/4" CCD	SONY 1/4" CCD	SONY 1/3" CCD	SONY 1/3" Super HAD CCD
Horizontal Resolution	420-480TVL				520TVL
Sensing Area	1/3": 4.9mm × 3.7mm / 1/4": 3.6mm × 2.7mm				
Scanning System	PAL(CCIR) / NTSC(EIA)				
Scanning System	PAL: 50Hz / NTSC: 60Hz				
Number of Pixels	PAL: 512(H) × 582(V) 512(H) × 492(V)	NTSC: 512(H) × 582(V) 512(H) × 492(V)	PAL: 500(H) × 582(V) 510(H) × 492(V)	NTSC: 500(H) × 582(V) 510(H) × 492(V)	PAL: 752(H) × 582(V) NTSC: 768(H) × 494(V)
Minimum illumination	0.05Lux				
Backlight Compensation	Auto				
Electronic Shutter	PAL: 1/50—1/100, 000S / NTSC: 1/60—1/100, 000S				
AGC	Auto				
Exposure Mode	EE/AI Switchable				
S/N Ratio	≥48db				
White Balance	Auto Follow				
Gamma Correction	>0.45				
Sync. System	Internal Synchronization				
Video Out	1.0 V P-P/75Ω				
Power Supply	DC12V ± 5%				
Current	≤120mA				
Operation Temperature	-10°C—+55°C				
Figure Dimension	Φ 86 × 55 (H) mm				