

HSS-H4 HOLE SAW

Model:SMI-HSS-H4



Specifcation:

▲Hollow Hole Saws

- 1.Usage:suitable for installing air conditions,water pipes,rainspouts,and etc
- 2.Surface treatment:Sand blasted,Blackoxide,Ti Coated,Metal shiny,etc

▲HSS Hole Saws

- 1.Special Feature:thebiggest cutting depth is 1.6mm
- 2.Surface treatment:NI Coated,Golden Finish,Metal shiny,Co Coated and etc

▲TCT Hole Saws

- 1.Special Feature:thebiggest cutting depth is 25mm
- 2.Surface treatment:Sand blasted,PEC and etc

▲Core Hole Saws

- 1.Special Feature:thebiggest cutting depth is 20mm
- 2.Surface treatment:Ni Coated and etc

▲Screwdrivers

- 1.Material:9CrSi,45#,Stwo
2. Usage:suitable for tightening and loosing filatures

Part NO.	METRIC	INCH	OVER RAU LENGTH	SHANK DIA
HSS-H4014	14	9/16 "	67	10
HSS-H4016	16	5/8 "	67	11
HSS-H4019	19	3/4 "	67	12
HSS-H4022	22	7/8 "	67	14
HSS-H4025	25	1 "	67	16
HSS-H4028	28	1-1/8 "	67	19
HSS-H4032	32	1-1/4 "	67	21
HSS-H4035	35	1-3/8 "	67	23
HSS-H4038	38	1-1/2 "	67	25
HSS-H4048	48	1-7/8 "	67	31
HSS-H4055	55	2-1/8 "	67	37
HSS-H4060	60	2-3/8 "	67	40
HSS-H4065	65	2-9/16 "	67	43
HSS-H4070	70	2-3/4 "	67	46
HSS-H4075	75	2-7/8 "	67	50
HSS-H4080	80	3-1/8 "	67	53