

HSS-H1 HOLE SAW

Model:SMI-HSS-H1



Specifcation:

▲Hollow Hole Saws

- 1.Usage:suitable for installing air conditions,water pipes,rainspouts,and etc
- 2.Surface treatment:Sand blasted,Blackoxide,Ti Coated,Metal shiny,etc

▲HSS Hole Saws

- 1.Special Feature:thebiggest cutting depth is 1.6mm
- 2.Surface treatment:NI Coated,Golden Finish,Metal shiny,Co Coated and etc

▲TCT Hole Saws

- 1.Special Feature:thebiggest cutting depth is 25mm
- 2.Surface treatment:Sand blasted,PEC and etc

▲Core Hole Saws

- 1.Special Feature:thebiggest cutting depth is 20mm
- 2.Surface treatment:Ni Coated and etc

▲Screwdrivers

- 1.Material:9CrSi,45#,Stwo
2. Usage:suitable for tightening and loosing filatures

Part NO.	METRIC	INCH	OVER RAU LENGTH	SHANK DIA
HSS-H1014	14	9/16"	55	10
HSS-H1016	16	5/8"	55	11
HSS-H1019	19	3/4"	55	12
HSS-H1022	22	7/8"	55	14
HSS-H1025	25	1"	55	16
HSS-H1028	28	1-1/8"	55	19
HSS-H1032	32	1-1/4"	55	21
HSS-H1035	35	1-3/8"	55	23
HSS-H1038	38	1-1/2"	55	25
HSS-H1048	48	1-7/8"	55	31
HSS-H1055	55	2-1/8"	55	37
HSS-H1060	60	2-3/8"	55	40
HSS-H1065	65	2-9/16"	55	43
HSS-H1070	70	2-3/4"	55	46
HSS-H1075	75	2-7/8"	55	50
HSS-H1080	80	3-1/8"	55	53