



HTS-506

The Hi-fi Front Speaker:

- Three-way and three units ● One 6.5" (165mm) Paper Cone Woofer with Rubber Surround
- One 4" (100mm) Paper Cone Woofer with Rubber Surround ● One 1" (25mm) Silk Dome Tweeter with Ferro Fluid ● Frequency Response: 50Hz~20KHz ● Sensitivity: 86dB
- Speaker Power: 60W ● Impedance: 6 ohms ● Dimension: 210x900x245 mm

Center Speaker:

- Two-way and three units ● Dual 4" (100mm) Paper Cone Woofer with Rubber Surround
- One 3/4" (19mm) Mylar Cone Tweeter ● Magnet-shielding Design ● Frequency Response: 100Hz-16KHz ● Sensitivity: 86dB ● Speaker Power: 40W ● Impedance: 6 ohms
- Dimension: 400x146 x156 mm

Bookshelf Speaker:

- Two-way and two units ● One 4" (100mm) Paper Cone Woofer with Rubber Surround
- One 3/4" (19mm) Mylar Cone Tweeter ● Frequency Response: 100Hz~16KHz
- Sensitivity: 86dB ● Speaker Power: 25W ● Impedance: 6 ohms
- Dimension: 140x 250x156 mm

Active Subwoofer:

- One 8" (203mm) Treated Paper Cone Woofer ● High/Low Level Input
- Frequency Response: 32Hz-150Hz ● Power: 75W