




VINYL INSULATED MULTI-STACK DISCONNECTOR




INSULATED PART MATERIAL:VINYL

METAL PART MATERIAL: BRASS

WIRE RANGE A..W.G./mm ²	PRODUCT CODE	MATES WITH FEMALE & MALE	DIMENSION (mm)				
		WIDTH X THICKNESS	W	B1	L	B	D
22-16A.W.G. 0.5-1.5mm ²	PBDV1-250	.032 X .250 (0.8 X 6.35)	6.6	6.4	22.5	10.0	3.8
16-14 A.W.G. 1.5-2.5mm ²	PBDV2-250	.032 X .250 (0.8 X 6.35)					4.7
12-10 A.W.G. 4-6mm ²	PBDV5-250	.032 X .250 (0.8 X 6.35)			24.0	13.0	6.2



NYLON INSULATED MULTI-STACK DISCONNECTOR



INSULATED PART MATERIAL:NYLON

METAL PART MATERIAL: BRASS

WIRE RANGE A..W.G./mm ²	PRODUCT CODE	MATES WITH FEMALE & MALE	DIMENSION (mm)				
		WIDTH X THICKNESS	W	B1	L	B	D
22-16A.W.G. 0.5-1.5mm ²	PBDNY1-250	.032 X .250 (0.8 X 6.35)	6.6	6.4	22.5	10.0	3.8
16-14 A.W.G. 1.5-2.5mm ²	PBDNY2-250	.032 X .250 (0.8 X 6.35)					4.7
12-10 A.W.G. 4-6mm ²	PBDNY5-250	.032 X .250 (0.8 X 6.35)			24.0	13.0	6.2