

Model No: 751TR

	Item	Value
GENERAL	Transmission Frequency	ISM 2,400~2,483 MHz
	Transmission Power	10mW/CE: 2mW/FCC
	Operating Frequency	2414MHz; 2432MHz; 2450MHz; 2468MHz
	Unobstructed Effective Range	100m(Min.)
	Modulation Mode	FM
	Operating Temperature	-10 ~ +50(Degree C) / +14 ~ +122(Degree F)
	Operating Humidity	≤85%RH
Transmitter GP-751T	BandWidth	18M
	Consumption Current	120mA (Max.)
	Power Supply	DC +8V
	Dimensions(W×D×H)	33*88*120 mm
	Weight	107g
RECEIVER GP-751R	Antenna	Built-in
	Receiving Sensitivity	≤-85dBm
	IR Remote Signal Transmission Frequency	433.92MHz
	IR Remote Signal Transmission Range	30m(Min.)
	Video Output Signal Level	1.1Vpp±0.2Vpp@75 ohm, S/N >38dB
	Audio Output Signal Level	3.0Vpp±1Vpp@600 ohm
	Consumption Current	220mA(Max.)
	Power Supply	DC +8V
	Dimensions(W×D×H)	33*88*120 mm
	Weight	115 g