

HYDRAULIC PRESS BRAKE

MODEL: SMI-WC67Y SERIES



FEATURES:

- ◆ Steel-welded construction, vibration to eliminate stress, with high strength and good rigidity.
- ◆ Hydraulic top-drive, steadiness and reliability. Mechanical stop, steel torsion bar to maintain synchronization, high precision.
- ◆ Motorized-adjusting device of backgauge and rams stroke, fine adjusting by handwheel, numerical display.
- ◆ Deflection compensation unit installed on the top die. Manual crowned bottom die holder is adopted for the machine above 250 tons length 4000mm.
- ◆ Travel limit protection. Full machine guarding with safety interlocker.

SPECIFICATIONS:

	Nominal Pressure	Length of working table	The distance of column	The depth of throat	Slide Stroke	Open Height	Working Speed	Motor power	Overall Dimensions
	kN	mm	mm	mm	mm	mm	mm/s	kW	mm
WC67Y-100/3200	1000	3200	2680	320	120	370	8	7.5	3280*1820*2430
WC67Y-100/4000	1000	4000	3280	320	120	370	8	7.5	4080*1820*2430
WC67Y-160/3200	1600	3200	2600	320	200	470	7	11	3260*1940*2660
WC67Y-160/4000	1600	4000	3400	320	200	470	7	11	4060*1940*2660
WC67Y-160/5000	1600	5000	4100	320	200	470	7	11	5060*1940*2800
WC67Y-160/5000	1600	6000	4800	320	210	520	7	11	6060*1940*3030
WC67Y-200/3200	2000	3200	2600	320	200	520	7	15	3260*1940*2865
WC67Y-200/4000	2000	4000	3400	320	200	520	7	15	4060*1940*2865
WC67Y-200/6000	2000	6000	4800	320	200	520	7	15	6060*2190*3070
WC67Y-250/3200	2500	3200	2700	400	250	560	7	18.5	3260*1990*3060
WC67Y-250/4000	2500	4000	3500	400	250	560	7	18.5	4060*1990*3060