

The followings are our Switching Mode Power Supplies. They are energy efficient and have Short Circuit Protection, Automatic Overload Cut off Functions. MW 7P12GTGS adopts a new exchangeable input system.

### MW 7E301GS 1200mA Primary Switched Plug-In Adaptor



Input Voltage: 100-240VAC 50/60Hz  
 Selectable Output Voltage: 3.0 / 4.5 / 6.0 / 7.5 / 9.0 / 12VDC  
 Regulated, 9.0VA (Max)  
 GS, CE Approved  
 Output Plug: 6XC detachable plugs  
 Dimension: 82x36x88mm  
 Packing: Individual colour giftbox

**Output Current:**

Output Voltage	For 240VAC input Output Current	For 100VAC Input Output Current
3.3V	1000mA	1200mA
4.5V	1000mA	1200mA
5.0V	1000mA	1200mA
6.0V	1000mA	1200mA
8.5V	1200mA	1200mA
7.1V	1200mA	1200mA


Pcs per Inner Ctn.	Pcs per Exp. Ctn.	Gross Weight (kg)	Net Weight (kg)	Dimension (cm)	CBM	Pcs per 20' Container
-	100	17.7	17	41x22x53	0.0478	59600



### MW 7P12GTGS Traveler 1200mA Primary Switched Plug-In Adaptor



Input Voltage: 100-240VAC ~ 50/60Hz  
 GS, CE, ETL, CB Approved  
 Selectable Output Voltage: 3.0 / 4.5 / 6.0 / 7.5 / 9.0 / 12VDC; 14.4VA (max)  
 Output Current: 1200mA (max)  
 Output Plug: 6XC detachable plugs  
 Dimension: 88x61x38mm  
 Packing: Individual colour giftbox



Pcs per Inner Ctn.	Pcs per Exp. Ctn.	Gross Weight (kg)	Net Weight (kg)	Dimension (cm)	CBM	Pcs per 20' Container
-	-	-	-	-	-	-

### MW 7E12GS 1200mA Primary Switched Plug-In Adaptor



Input Voltage: 100V-240VAC ~ 50/60Hz  
 GS, CE, ETL, CB approved  
 Selectable Output Voltage: 3.0 / 4.5 / 6.0 / 7.5 / 9.0 / 12.0VDC Regulated, 14.4VA (max)  
 Output Current: 1200mA (max)  
 Output plug: 6XC detachable plugs  
 Dimension: 82x36x88mm  
 Packing: Individual colour giftbox



Pcs per Inner Ctn.	Pcs per Exp. Ctn.	Gross Weight (kg)	Net Weight (kg)	Dimension (cm)	CBM	Pcs per 20' Container
-	100	20.8	19.8	41x22x53	0.0478	59616

### MW 7C20TGS 2000mA Primary Switched Plug-In Adaptor



Input Voltage: 100-240VAC ~ 50/60Hz 32W  
 GS, CE Approved  
 Selectable Output Voltage: 3.0 / 4.5 / 6.0 / 7.5 / 9.0 / 12.0VDC, 24.0VA(max)  
 Output Current: 2000mA (max)  
 Output Plug: 6XC detachable plugs  
 Dimension: 118x62x84mm  
 Packing: Individual colour giftbox



Pcs per Inner Ctn.	Pcs per Exp. Ctn.	Gross Weight (kg)	Net Weight (kg)	Dimension (cm)	CBM	Pcs per 20' Container
20	40	16.8	15.3	47x29x32	0.0436	29440