


工矿照明灯具系列
Factory and mining illumination fixture series
GC8



AC: 220~230V 50Hz


型号 Model	产品代码 Code	光源灯功率 Suitable for lamp	灯头 Base	PF≥0.85时线路电流 Circuit current at PF≥0.85 (A)	重量 Weight (kg)
HQBN-70/GC8	2520204003	MH/HPS 70W	E27	0.41	3.88
HQBN-150/GC8	2520209003	MH/HPS 150W	E27/E40	0.88	4.68
HQBN-250/GC8	2520212003	MH/HPS 250W	E40	1.47	5.68
HQBN-400/GC8	2520217003	MH/HPS 400W	E40	2.40	7.69



材质及特性

- 电器箱外壳采用高级小汽车用金属铁板，韧性好，耐冲击，重量轻。
- 外观简洁，明快，结构简单，更换电器方便、容易。
- 安装方便，只要把吊钩挂在外部的挂钩上，再上紧防脱螺丝即可。吊钩也可以更换成水管，由水管直接穿电源线到电器箱中也可，安装方式多样。
- 反光罩可根据不同的场所要求配置不同的反光罩，有宽光型，窄光型，及可在反光罩加装玻璃。
- 电器可根据客人要求，安装70W~400W间的光源。
- 电器箱四周增加了散热孔，使灯具具有良好的散热功能，能保证在正常使用时不会出现温度过高的现象，灯具按国家 GB7000.1-2002标准设计。

配光曲线
Luminous intensity curve



适用场所

- 工业厂房，体育场，商场，超市，候机大厅，候车大厅收费站。

Material & Characteristic

- Light metal sheet control gear with characteristics of good impact toughness
- Compact and concise appearance, easy appliance change
- Handy and various installation: clasp two hooks and fasten with screw, also can replace hooks with pipe to thread power wire into gear
- Selective reflector cover accordingly to the place: broad-light, narrow-light, explosion-proof type etc.
- Customized appliance for 70W~4000W lamp
- Good heat emitting holes around the gear to avoid high temperature during regular work; the fixture design and function are in accordance with relative secure and required national standards.

Applications

- Industrial workhouse, stadium, commercial piazza, supermarket, waiting hall, toll station etc.

