



## CHARACTERISTICS

- ⊙ 15" high brightness LCD screen, touch screen available (optional)
- ⊙ LCD brightness and contrast ratio adjustable by manual or automatic, standby power saving mode
- ⊙ High intensity Al-alloy panel, wire drawing hard anodic oxidation, stylish design
- ⊙ IP64 level overall defence, IP65 level front panel defence
- ⊙ Installation compatible with panel style, embedded style and VESA standard knighthead

## DIMENSION

**LCD:** TFT external VGA interface (LVDS internal)

**Luminance:** 350cd/m<sup>2</sup>

**Contrast Ratio:** 500:1

**Resolution:** 1024 × 768 maximum

**Response:** 16mS

**Power Supply:** External power supply

**Dimensions:** 400mm (W) × 300mm(H) × 40mm(D)

**Defence Level:** IP64 level overall defence, IP65 level front panel defence

## APPLICATIONS

Widely applied in the fields of telecommunication, electric power, multimedia, national defence, industrial automation equipment, manufactures and so on, as monitoring equipment.

## ORDERING INFORMATION

Model Number	Description
PDS-1502	15" LCD Flat Panel Display
PDS-1502-L	15" LCD Flat Panel Display (No OSD Function, Back-end Switch)

Images for references only, all product specifications are subject to change without notice.