

### Performance & Specification for High Precision CT07 Series 高精度CT07系列性能规格

| Part Number<br>型号 | Rated primary current (A)<br>额定初级电流 (A) | Max primary current(A)<br>最大初级电流 (A) | Rated secondary current(mA)<br>额定次级电流(mA) | Current ratio<br>电流变比 | Output voltage<br>输出电压(mv) | Accuracy class<br>精度等级(Class) | Outline<br>外形图 |
|-------------------|---|--------------------------------------|---|-----------------------|----------------------------|-------------------------------|----------------|
| CT07A             | 5                                       | 40                                   | 2.5                                       | 2000:1                | 100                        | 0.2,0.5                       | CT07A          |
|                   | 10                                      | 40                                   | 4   | 2500:1                | 100                        | 0.2,0.5                       |                |
| CT07D             | 20                                      | 40                                   | 10  | 2000:1                | 100                        | 0.1,0.2,0.5                   | CT07D          |
|                   | 10                                      | 60                                   | 4   | 2500:1                | 100                        | 0.1,0.2,0.5                   |                |
|                   | 20                                      | 60                                   | 10  | 2000:1                | 100                        | 0.1,0.2,0.5                   |                |
| CT07E             | 40                                      | 60                                   | 20  | 2000:1                | 100                        | 0.1,0.2,0.5                   | CT07E          |
|                   | 60                                      | 120                                  | 24  | 2500:1                | 100                        | 0.1,0.2,0.5                   |                |
|                   | 80                                      | 120                                  | 32  | 2500:1                | 100                        | 0.1,0.2,0.5                   |                |
| CT07F             | 120                                     | 120                                  | 48  | 2500:1                | 100                        | 0.1,0.2,0.5                   | CT07F          |
|                   | 100                                     | 200                                  | 40  | 2500:1                | 100                        | 0.1,0.2,0.5                   |                |
|                   | 100                                     | 200                                  | 50  | 2000:1                | 100                        | 0.1,0.2,0.5                   |                |
|                   | 200                                     | 250                                  | 80  | 2500:1                | 100                        | 0.1,0.2,0.5                   |                |

### Performance & Specification for Protection type Precision CT07 Series 保护型CT07系列性能规格

| Part Number<br>型号 | Rated primary current (A)<br>额定初级电流 (A) | Max primary current(A)<br>最大初级电流 (A) | Rated secondary current(mA)<br>额定次级电流(mA) | Resistance load<br>端接电阻 (ohm) | Output voltage<br>输出电压(V) | Accuracy class<br>精度等级(Class) | Outline<br>外形图 |
|-------------------|---|--------------------------------------|---|-------------------------------|---------------------------|-------------------------------|----------------|
| CT07A             | 5                                       | 60                                   | 5   | 100                           | 0.5                       | 0.5,1.0                       | CT07A          |
|                   | 10                                      | 60                                   | 10  | 100                           | 1                         | 0.5,1.0                       |                |
|                   | 15                                      | 60                                   | 15  | 100                           | 1.5                       | 0.5,1.0                       |                |
| CT07D             | 20                                      | 60                                   | 20  | 100                           | 2                         | 0.5,1.0                       | CT07D          |
|                   | 25                                      | 75                                   | 25  | 100                           | 2.5                       | 0.5,1.0                       |                |
|                   | 30                                      | 75                                   | 30  | 100                           | 3                         | 0.5,1.0                       |                |
| CT07E             | 40                                      | 75                                   | 40  | 100                           | 4                         | 0.5,1.0                       | CT07E          |
|                   | 50                                      | 125                                  | 50  | 100                           | 5                         | 0.5,1.0                       |                |
|                   | 60                                      | 125                                  | 60  | 100                           | 6                         | 0.5,1.0                       |                |
| CT07F             | 75                                      | 125                                  | 75  | 100                           | 7.5                       | 0.5,1.0                       | CT07F          |
|                   | 100                                     | 250                                  | 100                                       | 100                           | 10                        | 0.5,1.0                       |                |
|                   | 150                                     | 250                                  | 150                                       | 100                           | 15                        | 0.5,1.0                       |                |

#### Remarks

#### 备注

1. While In application of power transducer, RTU, please refer to 《Current Transformer Application Direction》
2. Customized orders are welcomed.
1. 用于电量变送器, RTU时, 请参阅: P1 《电流互感器使用说明》
2. 可以根据客户要求定做。