




■特点

- 适用于频率为50HZ/60HZ交流电源供电的单相异步电动机起动和运转
- 有自愈特性
- 性能稳定,可靠性高
- 防爆设计,更安全

■Features

- Widely applied to starting and running of AC single-phase synchronism motors at 50Hz/60Hz frequency power
- Self-healing property
- Excellent stable pertomance and reliability
- Anti-esollosion dasign, more safety

■技术要求Specifications

引用标准 Reference Standard	GB 3667 (IEC60252-1)	
气候类别 Climatic Category	40/70/21	
规定电压 Rated Voltage	250VAC, 300VAC, 350VAC, 400VAC, 50/60Hz	
电容量范围 Cepacitance Range	1.0uF~30.0uF	
电容量偏差 Capacitance Tolerance	±5%, ±10%, ±20%	
耐电压 Voltage Proof	引线之间Between Terminals:	787.5VAC (5s)
	极壳之间Between Ternianls And Case:	2000VAC (60s)
损耗角正切 Disslpation Factor	≤ 0.0020 (50Hz~100Hz) ≤ 0.0060 (1KHz, $C \leq 33\mu\text{F}$) ≤ 0.0080 (1KHz, $C > 33\mu\text{F}$)	
绝缘电阻 Insulation Resistance	$\geq 3000\text{s}$ (20°C, 100V, 1min)	