

Model No: 8601Q

	Item	Value
GENERAL	Transmission Frequency	ISM 2.400-2.483 MHz
	Transmission Power	10mW/CE; 2mW/FCC
	Operating Frequency	2414MHz; 2432MHz; 2450MHz; 2468MHz
	Unobstructed Effective Range	100m(Min.)
	Modulation Mode	FM
	Operating Temperature	0 ~ +50(Degree C) / +32~ +122(Degree F)
	Operating Humidity	≤85%RH
CAMERA	Imaging Sensor Type	CMOS
	Picture Total Pixels	NTSC: 720×480 Pixels; PAL: 720×576 Pixels
	Minimum Illumination	0Lux
	BandWidth	18M
	Night Vision Range	5m
	Horizontal Rotating Angle	270° (Max.)
	Vertical Rotating Angle	120° (Max.)
	Consumption Current	300mA (Max.)
	Power Supply	DC +9V
	Dimensions(W×D×H)	114*125*106 mm
	Weight	290 g
RECEIVER	LCD Screen Type	2.5 inches TFT-LCD
	Effective Pixels	640×240
	Receiving Sensitivity	≤ -85dBm
	Video System	NTSC/PAL
	Color Configuration	R.G.B.delta
	Remote Control Transmission Frequency	433MHz
	Consumption Current	200mA(Max.)
	Power Supply	DC +9V
	Dimensions(W×D×H)	68*26*149 mm
	Weight	168 g