

**Description:** Wireless Fixed Terminal with GIII Fax function



1. Support GSM 850/1900MHz,900/1800MHz automatically
2. Caller ID show in the LCD of external phone
3. Signal indicator and power indicator,Network Connection Status indicator,Power Status(on/off) indicator
4. SMS function(support Receive and Send short messages via PC
5. IP No. setting
6. Software upgrade jack
7. Data serve, Support GPRS class 10/8. Connect PC by RS232(DB9) port, optional
8. Call in / Call out /Call divert/ Call waiting limitation function
9. Lock up function: SIM card, network,Lock terminal
10. Local No. / direct No. / limited No. setting
11. Support G3 analog Fax,RJ-11 port
12. Support Reverse-polarity signal
13. Support three-way conference call
14. Emergency dialing
15. SMA connector can connect Yagi ant. optional
16. Support to setup parameters by keys(hidden code)
17. Resume to Factory setting state,Check settings

1	Colors:	Black/optional
2	Net Weight (Kg):	750 kg
3	Gross Weight (Kg)	950 kg
4	Piece by Carton:	10
5	Packing Size (mm)	193*131*42 (mm3)

**Quotation**

**Technical Parameter**

- Operating Requirements**
1. Normal operation temperature:-30° C ---70° C  
Permitted operation temperature: 0° C --- 50° C
  2. Enviroment noise: below 60dB(A)
  3. Relative humidity:45%~95%
  4. Atmosphere pressure:86~106KPa
  5. Support for software upgrade on line
  6. AC power voltage:110V-240V AC, Freq. :50
  7. GPRS multi-slot class 10/8
  8. GPRS mobile station class B
  9. Compliant to GSM phase 2/2+  
-Class 4(2W)850/900MHz  
-Class 1(1W)1800/1900MHz
  10. Control via AT commands  
(GSM 07.07,07.05 and SIMCOM enhanced AT Commands)
  11. Phone: DC 12V 1000mA
  12. Battery: 7.2V 1300mAH Ni-MH rechargeable battery(accessory)
  13. 1.With battery , standby time is more than 8h

<b>GIII Fax jack</b>	RJ-11*2		<b>Software update jack</b>	RJ-45*1
The RJ-11 Phone Port also support FAX			<b>external phone jack</b>	RJ-11*1
<b>CID standard:</b>	Yes		<b>Quotation</b>	
<b>Solution</b>	ADI		<b>MOQ</b>	5K
<b>FOB</b>	Shenzhen		<b>power supply</b>	220V

2. With battery, Call time is more than 2h

**Technology Parameter**

- 1 Operating Freq.:850/900/1800/1900MHz automatically switch
- 2 Support SIMCard 1.8V/ 3V
- 3 Channel interval:200KHz
- 4 Receive sensitivity:<-102dBm
- 5 Freq. error:<=0.1ppm