

SURFACE-MOUNT WOUND COMMON MODE CHOKES SF0805 1206 & CM01-02 SERIES

FEATURES:

- Ferrite Core bobbin construction
- High frequency and Large current
- Excellent Mechanical Strength
- Excellent Solderability
- Excellent Frequency performance
- Low Profile and Low cost

OPTIONS:

- Packaging:Tape & Reel is standard (Qty:2000pcs)
- Bulk packaging available for smaller quantities
- Tolerance:20% is standard, tighter tolerances available

COMMON APPLCATIONS:

- DC/DCAC/DC convertor
- Video Cameras
- Communication System
- Automotive Systems
- Liquid Crystal Televisions
- Hard Disk Drives
- Network Systems
- Computer Peripheral Equipment

ELECTRICAL CHARACTERISTICS:

Part Number	Common Mode Impedance @100MHz (Ω)+/-20%	IDC Max A	DCR mΩ Max	Rated Voltage VDC	Wistanding Voltage (CH-901)	Part Number	Common Mode Impedance @100MHz (Ω)TYPE	IDC Max mA	DCR mΩ Max	Rated Voltage VDC	Wistanding Voltage (CH-901)
CM01-301M	300	2.5	25	80	AC150V 2mA/1min	SF0805-670	47Ω(67Ω)	400	0.25	50	125VDC
CM02-501M	500	5.0	10	80		SF0805-900	63Ω(90Ω)	330	0.35	50	125VDC
CM02-801M	800	3.5	20	80		SF0805-121	84Ω(120Ω)	370	0.30	50	125VDC
CM02-102M	1000	2.5	50	80		SF0805-181	126Ω(180Ω)	330	0.35	50	125VDC
						SF0805-261	182Ω(260Ω)	300	0.40	50	125VDC
						SF0805-371	259Ω(370Ω)	280	0.45	50	125VDC
						SF1206-900	63Ω(90Ω)	370	0.30	50	125VDC
						SF1206-161	112Ω(160Ω)	340	0.40	50	125VDC
						SF1206-261	182Ω(260Ω)	310	0.50	50	125VDC
						SF1206-601	420Ω(600Ω)	260	0.80	50	125VDC
						SF1206-102	700Ω(1000Ω)	230	1.00	50	125VDC
						SF1206-222	1540Ω(2200Ω)	200	1.20	50	125VDC


Note:1. K= ± 10%,M= ± 20%,N= ± 30%

TECHNICAL INFORMATION & PHYSICAL CHARACTERISTICS:

- Inductance Testing: 1KHz 1V HP4284A
- Z test with HP4191A or HP4395A
- RDC:QuadTech 1880 Milliohmeter
- Operating temperature: -40°C to +105°C
- Storage Temperature: -40°C to +105°C
- Resistance to soldering heat:260°C for 10 seconds
- Marking: Part number and date code

Note:All specifications subject to change without notice.

DIMENSIONS IN:mm



Part Number	A	B	C	D	E	F	G	H	I
SF0805	2.060.2	1.2 ± 0.2	1.1 ± 0.2	0.45	0.4	2.6	0.8	1.3	0.4
SF1206	3.260.2	1.6 ± 0.2	1.4 ± 0.2	0.60	0.6	3.8	1.6	1.6	0.4

Note:All specifications subject to change without notice.