

## Alkaline Button Cell - Standard

### 硷性钮扣式电池

#### BATTERY SPECIFICATION

#### 电池规格



Model No.	Fty. Ref.	Nominal Voltage	Dimensions (mm)		Average Weight	Cross Reference				
			尺寸 (毫米)			其他厂家参考编号				
型号	本厂编号	标准电压 (V/伏)	Diameter	Height	平均重量 (g/克)	IEC	Eveready	Varta	Ray-O-Vac	Maxell
			直径	高		国际标准				
357A	AG13	1.5	11.60	5.40	1.95	LR44	A76	4276(V13GA)	RW82	LR44
386A	AG12	1.5	11.60	4.2	1.58	LR43	186	4278(V12GA)	RW84	LR43
361A	AG11	1.5	7.85	2.15	0.40	-	-	-	-	-
389A	AG10	1.5	11.60	3.05	1.16	LR54	189	4274(V10GA)	RW89	LR1130
394A	AG9	1.5	9.5	3.60	0.87	-	-	-	-	-
391A	AG8	1.5	11.60	2.05	0.87	LR55	191	V8GA	-	LR1120
399A	AG7	1.5	9.5	2.60	0.65	-	-	-	-	-
370A	AG6	1.5	9.5	2.10	0.54	-	-	-	-	-
393A	AG5	1.5	7.85	5.40	0.94	-	193	-	-	-
377A	AG4	1.5	6.80	2.60	0.34	-	-	-	-	-
392A	AG3	1.5	7.85	3.60	0.64	LR41	192	V3GA	-	LR41
396A	AG2	1.5	7.85	2.60	0.47	-	196	-	-	LR726
364A	AG1	1.5	6.80	2.10	0.28	-	-	-	-	-
321A	AG1X	1.5	6.80	1.60	0.21	-	-	-	-	-
379A	379A	1.5	5.80	2.15	0.22	-	379	V379	379	LR521
625A	AG625	1.5	15.00	6.05	3.45	-	-	246	-	-

## Alkaline Button Cell - Heavy Duty

### 硷性钮扣式电池 - 高容量级

#### BATTERY SPECIFICATION

#### 电池规格



Model No.	Fty. Ref.	Nominal Voltage	Dimensions (mm)		Average Weight	Cross Reference				
			尺寸 (毫米)			其他厂家参考编号				
型号	本厂编号	标准电压 (V/伏)	Diameter	Height	平均重量 (g/克)	IEC	Eveready	Varta	Ray-O-Vac	Maxell
			直径	高		国际标准				
LR44H	AG13	1.5	11.60	5.40	1.93	LR44	A76	42769V13GA)	RW82	LR44
LR43H	AG12	1.5	11.60	4.20	1.48	LR43	186	43278(V12GA)	RW84	LR43
LR1130H	AG10	1.5	11.60	3.05	1.10	LR54	189	4274(V10GA)	RW89	LR1130
LR1120H	AG8	1.5	11.60	2.05	0.72	LR55	191	V8GA	-	LR1120
LR41H	AG3	1.5	7.85	3.60	0.61	LR41	192	V3GA	-	LR41