

Model Name	DV927HD	
Solution	MTK1389FE/ (S) +64M SDRAM+16M FLASH+AM5888+ SONY 313A pick-up	
General	● Super compatibility with DVD Video, VCD, HDCD, SVCD, CD, CD-R/-RW, DVD-R/-RW, Kodak Picture CD, MP3, OGG, WMA	
	● MPEG4 standard support: compatibility with DivX3.11, DivX4, DivX5, DivXpro, XviD	
	● KARAOKE + system ,expanding karaoke function	
	● "Memory" function enable to save the last point after stop playback	
	● "Q-Play" function provides direct and allow to skip commercial that is not possible to rewind	
	● "Virtual keyboard" function provides more convenient DVD playback control	
	● "Browse" function provides easy access to playback control	
	● USB 2.0 port	
	● Automatic Screensaver.	
	● Super Wide range of operating power suppliers (~ 110-250 V, 50/60 Hz), automatic short circuit protection	
● Parental control function.		
Video	● Capable of playing PAL/NTSC discs	
	● HDMI interface provides high-definition image(1080p)and digital audio	
	● 108MHz/12bit video D/A converter	
	● NTSC/PAL Video Output	
	● Screen aspect ratio selectable(4:3 and 16:9)	
	● Smart Video: Sharpness/Contrast/Brightness/HUE/Saturation/Gamma adjust	
	● Multi-angled view	
● Multi-language for OSD		
Audio	● Stereophonic output, 5.1CH output	
	● 192KHz/24bit audio DAC	
	● Coaxial output from Dolby digital and DTS, LPCM digital audio	
	● Digital audio playback: DVD-Audio, CD-DA and HDCD compatibility	
	● Built-in Dolby prologic II decoders makes available to convert stereo signal into multi-channel	
	● Mix output for amplifier or TV connect	
	● Dolby Digital/Dolby prologic II /DTS/LPCM Bitstream Output	
	● 3D surround (virtual surround): Concert, Living Room, Hall, Bathroom, Cave, Arena, Church	
	● Smart E.Q.(sound effect): Rock, POP, Live, Dance, Techno, Classic, Soft	
● Headphone output		
Hardware	DVD DECODER	MTK1389FE/ (S)
	Memory (Flash)	16M(bits)
	Memory (DRAM / SDRAM / SRAM)	16M*4bits
	D/A converter for Video	MTK1389FE/ (S)
	Pickup	Sony pickup ,313AAA
Connectors	MIC input	1
	USB	1
	Mix out	1
	Coaxial out	1
	Optical out	1
	S-Video out	1
	Video out	1
	YPbPr	1
	Headphone out	1
	HDMI	1
	SCART	1
Environmental	Operating temperature	5~35°C

Environmental Condition	Operating Humidity	15~75%
	Voltage range	~110-250 V, 50/60 Hz
Accessories	Remote control	1pcs,
	Audio 2*RCA--2*RCA cord	1pcs
	Video RCA--RCA cord	1pcs
	Video cord HDMI-HDMI	1pcs
	AAA size battery	2pcs
Packing	420*236.5*39mm3	
Weight	2.3kg	