




PIN	C1	C2	C3	C4
1	1D	1E	1F	1A
2	1C	1G	1B	S1
3	2D	2E	2F	2A
4	2C	2G	2B	S2
5	3D	3E	3F	3A
6	3C	3G	3B	S3
7	4D	4E	4F	4A
8	4C	4G	4B	S4
9	5D	5E	5F	5A
10	5C	5G	5B	S5
11	6D	6E	6F	6A
12	6C	6G	6B	S6
13	S11	S12	S13	S14
14	T2	T1	T0	T31
15	T3	T4	T5	T6
16	T10	T9	T8	T7
17	T11	T12	T13	T14
18	T18	T17	T16	T15
19	T19	T20	T21	T22
20	T26	T25	T24	T23
21	T27	T28	T29	T30
22	S7	S8	S9	S10
23	C1			
24		C2		
25			C3	
26				C4



1. DISPLAY TYPE	TN/POSITIVE	5. OPERATIVE VOLTAGE	3.0 V	APPROVED BY		CUSTOM NO.		UNITS	mm
2. VIEWING DIRECTION	12 O'CLOCK	6. OPERATIVE TEMP.	-30° C TO 85° C	CHECKED BY		DESIGN NO. & (VERSION)	SEQ0171/05 (A5)	SCALE	
3. POLARIZER MODE	TRANSFLECTIVE	7. STORAGE TEMP.	-35° C TO 85° C	DRAWING BY	LMX	MODEL NO.	I7808DF	SHEET	1 OF 1
4. DRIVE METHOD	1/4 DUTY 1/3 BIAS	8. CONNECTOR	PIN	REMARK					FAX NO.: 0755-82262915

深圳市新深辉显示技术有限公司
CHINA DISPLAY TECHNOLOGY CO., LTD