

VPZ series (Standard Conductive Polymer Aluminum Solid Electrolytic Capacitor of V-Chip Type,105°C,2000 hours,Extra Low ESR,High Ripple Current Capability)

Rated Voltage(V)	Capacitance(uF)	Part Number	Leakage Current(uA)	Tanδ(120Hz)	ESR(mΩ)	Max.Ripple Current (mA _{rms})	ΦD X L (mm)
					100-300KHz 20°C	100KHZ at 105°C	
2.5	680	VPZ0E681M0812	340	0.18	13	4520	8 X 11.8
	1000	VPZ0E102M1013	500	0.18	13	5200	10 X 12.7
	1500	VPZ0E152M1013	750	0.18	12	5440	10 X 12.7
	2700	VPZ0E272M1013	1350	0.18	15	5600	10 X 12.7
4	560	VPZ0G561M0812	448	0.18	13	4520	8 X 11.8
	1200	VPZ0G122M1013	960	0.18	12	5440	10 X 12.7
	2200	VPZ0G222M1013	1760	0.15	11	7200	10 X 12.7
6.3	470	VPZ0J471M0812	592	0.15	15	4210	8 X 11.8
	820	VPZ0J821M1013	1033	0.15	12	5440	10 X 12.7
	1500	VPZ0J152M1013	1890	0.15	12	5560	10 X 12.7
10	330	VPZ1A331M0812	660	0.15	17	3950	8 X 11.8
	560	VPZ1A561M1013	1120	0.15	13	5230	10 X 12.7
16	100	VPZ1C101M0812	320	0.15	25	3320	8 X 11.8
	150	VPZ1C151M1013	180	0.15	20	4320	10 X 12.7