

# UE05WCP-SPA

## USB Switching Power Adaptor

5 Watt

### Technical data

Input voltage	100-240V AC
Input current	200mA
Frequency	50-60Hz
Efficiency	meets CEC requirements
Output voltage tolerance	± 5%
Low standby power	0.3W Max.

### Environmental specification

Operation temp.	0°C to 40°C at maximum load
Storage temp.	-20°C to 60°C
Humidity	5% to 95% non condensing

### Safety specification

Safety approval	cULus (UL6500 and CSA60065) TUV-GS (EN60065) CE Mark (EN60065) PSE-JET C-Tick (AS/NZS60065) K-Mark CCC (GB8898) TLC (YD/T1591-2006)
-----------------	--

### Reliability specification

MTBF calculation	50,000 hours at maximum load levels and an ambient temperature of 25°C (in correspondence with MIL-HDBK-217)
------------------	--

### Mechanical specification

Weight	51g (not including AC plug) AC plug for China, USA, Japan: 10g AC plug for EU: 17g AC plug for Korea: 19g AC plug for UK: 27g AC plug for Australia: 15g
--------	---





Dimensions	72.0mm x 43.0mm x 26.0mm (2.83" x 1.69" x 1.02")
------------	---



### Output Data

Model	Voltage (V)	Current (A)	Ripple (mV)
UE05WCP-050YYYYSPA	5.0	0.10-1.00	50

YYY: 010-100 stands for current: 0.10A-1.00A




China




USA




Australia



UK



EU



Korea



UE Electronic

### 東莞市石龍富華電子有限公司

中國廣東省東莞市石龍鎮新城區黃洲祥龍路富華電子工業園

Fuhua Electronic Industrial Park, Xianglong Road, Huangzhou, New Town District,  
Shilong Town, Dongguan, Guangdong Province, China. 523326  
Tel: (86) 769 86022222 Fax: (86) 769 86023333  
www.fuhua-cn.com E-mail: fuhua@fuhua-cn.com

### Fuhua Electronic (HK) Co., Ltd.

香港九龍彌敦道27-33號良士大廈9樓H室

Flat H, 9/F., Alpha House, 27-33 Nathan Road,  
Kowloon, Hong Kong.  
Tel: (852) 27391666 Fax: (852) 27395999  
www.fuhua.com.hk E-mail: fuhua@fuhua.com.hk