

## CDMA Wireless Local Loop Phone



HWCD399 (123) CD

### Specification

- ◆ LCD B/W 128×64 matrix display with status icons
- ◆ 450/800/1900MHz, w/o UIM card with or without 1X data optional,
- ◆ LCD: B/W segment display
- ◆ Locked to specified operator, cell lock, interlock of phone and UIM cards
- ◆ Electric shock-resistant protection,
- ◆ AC adopter with rechargeable battery pack, low power consumption design
- ◆ Talk time: about 3 hours
- ◆ Standby time: about 120 hours
- ◆ Receiving sensitivity: -104 dBm
- ◆ Max. transmission power: 23 dBm
- ◆ Dipole antenna, External antenna optional

### Functions:

- ◆ Caller ID, Call hold, Call forwarding and Call barring
- ◆ Three-party call
- ◆ Speaker phone
- ◆ Last number redial
- ◆ Recent call & Call Timer
- ◆ Speed dialing with a 99-numbers memory
- ◆ 10 ring tones selectable
- ◆ Ring and voice volume adjustable
- ◆ Scheduler, stopwatch, and alarm functions
- ◆ Phonebook: 150 (3 numbers each entry)
- ◆ SMS: 55 (35 inbox + 20 outbox)
- ◆ DB9/F data port for 1x data access, software update and phone settings
- ◆ English and Spanish manual available

Shenzhen Gaoxinqi Technology Co. Ltd,

Address: Gaoxinqi Industrial Park, Liuxian 1st Road, district 67, Bao'an, Shenzhen, P. R. China

Tel: +86-755-29619999, [www.gaoxinqi.com](http://www.gaoxinqi.com), contact: [alex@gaoxinqi.cn](mailto:alex@gaoxinqi.cn)