

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
COM1	X2	1F	1A	2F	2A	9F	9A	10F	10A	11F	11A	12F	12A	13F	13A	S12	S22	X5				COM1
COM2	X3	1G	1B	2G	2B	9G	9B	10G	10B	11G	11B	12G	12B	13G	13B	S10	S21	S13			COM2	
COM3	X4	1E	1C	2E	2C	9E	9C	10E	10C	11E	11C	12E	12C	13E	13C	S11	S20	X6		COM3		
COM4	X1	S4	1D	S3	2D	S17	9D	S8	10D	DP8	11D	DP9	12D	S9	13D	S18	S19	S14	COM4			

PIN	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44
COM1	AA	var	8A	8F	7A	7F	N	C	COSφ	T23	T20	T19	T18	6A	6F	5A	5F	4A	4F	3A	3F	S6
COM2	S16	h	8B	8G	7B	7G	T24	B	A	T22	T21	DP5	T17	6B	6G	5B	5G	4B	4G	3B	3G	S1
COM3	S15	T15	8C	8E	7C	7E	T14	T11	T10	T7	T6	T3	T2	6C	6E	5C	5E	4C	4E	3C	3E	S2
COM4	K	T16	8D	DP7	7D	DP6	T13	T12	T9	T8	T5	T4	T1	6D	DP4	5D	DP3	4D	DP2	3D	DP1	S5

NOTE[●]:ABOUT 5 CROSSPOINTS IN V.A(0.08mmX0.08mm)

深圳市新深辉显示技术有限公司
CHINA DISPLAY TECHNOLOGY CO.,LTD

1. DISPLAY TYPE	FSTN/POSITIVE	5. OPERATIVE VOLTAGE	3.2 V	APPROVED BY			CUSTOM NO.		UNITS	mm
2. VIEWING DIRECTION	6 O'CLOCK	6. OPERATIVE TEMP.	-20° C TO 70° C	CHECKED BY			DESIGN NO. & (VERSION)	SEQ1061/04(A1)	SCALE	
3. POLARIZER MODE	TRANSFLECTIVE	7. STORAGE TEMP.	-30° C TO 80° C	DRAWING BY	ljun	2007-1-3	MODEL NO.	FSTN7576FT(DU)/X(P3)	SHEET	1 OF 1
4. DRIVE METHOD	1/4 DUTY 1/3 BIAS	8. CONNECTOR	PIN	REMARK					FAX NO.:0755-82262915	