

Model No: 840J

	Item	Value
GENERAL	Transmission Frequency	ISM 2,400~2,483 MHz
	Transmission Power	10mW/CE; 2mW/FCC
	Operating Frequency	2414MHz; 2432MHz; 2450MHz; 2468MHz
	Unobstructed Effective Range	100m(Min.)
	Modulation Mode	FM
	Operating Temperature	-10 ~ +50(Degree C) / +14~ +122(Degree F)
	Operating Humidity	≤85%RH
CAMERA	Imaging Sensor Type	CMOS
	Picture Total Pixels	PAL: 628×582 Pixels; NTSC: 510×492 Pixels
	Minimum Illumination	0Lux
	Night Vision Range	3m
	Li-battery Charge Time	2hours
	Li-battery Working Time	5hours(IR OFF)/2hours(IR ON)
	BandWidth	18M
	Power Supply	DC +5V
	Dimensions(Diameter×D)	30*87 mm
	Weight	125g
RECEIVER	Antenna	50 ohm SMA
	Receiving Sensitivity	≤-85dBm
	Video Output Signal Level	1.1Vpp±0.2Vpp@75 ohm, S/N >38dB
	Audio Output Signal Level	3.0Vpp±1Vpp@600 ohm
	Intermediate Frequency	480MHz
	Consumption Current	190mA(Max.)
	Power Supply	DC +8V
	Dimensions(W×D×H)	16*102*80mm
Weight	120 g	