


CT300KD		Specifications	
		ENGINE	
		Displacement (cm <sup>3</sup> )	287.2
		Cooling Mode	Sanyang Brand;Water-cooled
		Bore x Stroke(mm)	75 x 65
		Compression Ratio	10.0 : 1
		Standard Power(KW/R/Min)	14.2kw/6000rpm
		Maximum Torque(N.m/r/min)	24.5/5000r/min
		Carburetion	PZ30M
		Ignition Type	CDI
		Start Mode	Electric
		Transmission	CVT
		Drive Train	Chain
		CHASSIS	
		Frame Mode	Pipe Board Mode
Tire Size(Front)	23 x 7-10		
Tire Size(Rear)	25 x 10-12		
Brake(Front)	Disc		
Brake(Rear)	Disc		
DIMENSIONS			
Dim(LxWxH)(mm)	2340 x 1620 x 1590		
<b>Certificate</b>		Dead Weight(kg)	384
EEC	NO	Max.Weight(kg)	534
EPA	NO	Wheel Base(mm)	1720
CARB	NO	Ground Clearance(mm)	205
		Turning Radius(mm)	3930
		Fuel tank Capacity(L)	15
		Loading Quantity	20'GP/8pcs; 40'HQ/27pcs
<b>Optional</b>		OTHER	

	Max.Speed(km/h)	63
	Battery(V.Ah)	YTX12-BS
	Headlight/Turning Light	12V/35W/35W; 12V35W
	Brake Light/Taillight	12V/21W/5W