

**CT250****Specifications****ENGINE**

Type	Water-Cooled, 4-Stroke
Displacement (cm <sup>3</sup> )	244
Bore x Stroke(mm)	72 x 60
Compression Ratio	10:01
Standard Power(KW/R/Min)	10.5kw/6000rpm
Maximum Torque(N.m/r/min)	17.6/5500r/min
Lubrication	Force&Splash
Ignition Type	DC.D.I
Start Mode	Electric
Lubricate Oil	SAE15W-40/SF
Transmission	Automatic(C.V.T system)

**CHASSIS**

Rear Brake	Hydraulic Disc,Left Foot Control
Font Tire	AT21 x 8-10
Rear Tire	AT22 x 10-10
Tire Pressure (Front)	150kPa
Tire Pressure (Rear)	150kPa

**DIMENSIONS**

Dim(LxWxH)(mm)	2340 x 1660 x 1485
Wheelbase(mm)	1795
Front Track(mm)	1460
Rear Track(mm)	1345
Ground Clearance	255
Net Weight(kg)	370
Gross Weight(kg)	440
Loading Quantity	40'HQ/30pcs

**Quotation**

EEC NO  
EPA YES  
CARB NO

**Optional**

OTHER

	Max.Speed(km/h)	65
	Battery(V.Ah)	12V14Ah
	Headlight	2-12V/35W/35W
	Taillight	2-12V/21W/5W