

Truck Tyre Changer

(CE)**Model: LT650**

Technical data:

Applicable to 14" – 26"

Suitable for various tyres of large vehicle, applicable to tyres with ring and layering, the meridian vacuum tyre, the agriculture uses the tyres, such as the machine and the engineering machine etc.

It can save human resource, work time and energy with high efficiency. No need to strike the tyres with big hammers, no damage to wheel and rim.

Really an ideal choice for tyre repairing & maintenance equipment.

Mount/Demount arm enables the work easy and relaxing.

29F, NEW WORLD MANSION, 9, FUZHOUNAN ROAD, QINGDAO, CHINA. POSTAL-CODE: 266071

Tel: 0086-532-85712555 Fax: 0086-532-85724659

The modern wireless remote-control makes the operation much more convenient.

Operating voltage 24V, safe & stable.

Specification:

Model	LT650
Application range	Truck/Bus/Tractor/Industry vehicle
Max. wheel weight	500kg
Max. wheel width	780mm
Max. outer diameter of tyre	1600mm
Clamping range	14'' ~ 26''(355 ~ 660.4mm)
Driving power of hydraulic pump	1.1KW 380V 3PH
Driving power of gear motor	1.8KW 380V 3PH
Min. inner diameter of rim	130 ~ 510mm
Max. sliding distance of mount/demount arm	48'' (1214mm)
Operation voltage	24V
Rotation speed	7.34rpm
Bead-loosening force	2500kg



Working pressure	13Mpa ~ 20Mpa
Clamping force	4000kg
Noise	<70Db
N.W./G.W.	585kg/640kg
Packing size:	199 x 160 x 88cm