

## Tyre Changer

**[CE]**

**Model: LT980A**



### **Technical data:**

**Suitable for 12 inch to 24 inch stiff, wide, flat and low-profile tyres.**

**With self-centering function.**

**Clamping system with stepping function.**

**With quick inflation device for tubeless tyres.**

**Articulated mount arm.**

**With adjusting & calibrating functions in the 4 clamps on the turntable.**

**Rubber-pad mount/demount head.**

**Angles of mount/demount head can be adjusted & calibrated.**

**Polymer mount/demount head of high quality prevent damage to the rim (optional).**

**Specification:**

<b>Model</b>	<b>LT980A</b>
<b>Power supply/Motor power</b>	<b>110V/220V/380V 1.1/0.75KW</b>
<b>Pneumatic supply</b>	<b>0.8~1.2Mpa</b>
<b>Rim clamping range (External)</b>	<b>12''~22''</b>
<b>Rim clamping range (Internal)</b>	<b>14''~24''</b>
<b>Bead loosening force</b>	<b>2500kg</b>
<b>Max. wheel diameter</b>	<b>1100mm</b>
<b>Max. wheel width</b>	<b>15''</b>
<b>Noise</b>	<b>&lt;70Db</b>
<b>N.W./G.W.</b>	<b>355kg/436kg</b>
<b>Packing size</b>	<b>109 x 94 x 92cm</b>