

Speed Dome Camera Controller

Products List > D Series > Speed Dome Camera > Speed Dome Camera Controller > MCU-PTZ031, MCU-PTZ033

MCU-PTZ031, MCU-PTZ033

FEATURES




MCU-PTZ031

- ◆ RS485/232 Communication
- ◆ Variable PTZ Speed
- ◆ Easy & Simple Installation

MCU-PTZ033

- ◆ System Control with Video Switcher System
- ◆ System Integration via RS-485
- ◆ Programmable Camera Functions
- ◆ Remote Control of all Additional Functions



Tol: ±0.5 Unit:mm

SPECIFICATIONS

	MCU-PTZ031	MCU-PTZ033
Power Supply	12Vdc, 900mA	9~12Vdc, 600mA
Output Control	Maximum 32 Speed dome cameras or receivers	
Function Display	LCD	
Keys and Joystick	Switch Keys: ON, OFF Number Keys: 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, Enter Camera Control: Joystick Pan-tilt (Variable Speed) OPEN, CLOSE, AUTO, FAR, NEAR, WIDE, TELE Function Keys: SHOT, PRESET, CALL, TIME, CAM Special Function Keys: F1	Number Keys: 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, *, MON, CAM, CLR, ENTER Function Keys: ALM, GRP, OFF, ON, AUTOPAN, AUX, RUN, HOLE, PREV, NEXT Special Function Keys: DVR, MUX, MENU, S ET, SHOT Light: POWER, DVR, TX, MUX, Rx, SYS Lens Control: ZOOM, FOCUS, IRIS Joystick: 5 Function Pan/Tilt/3D Control: UP, DOWN, RIGHT, LEFT, ZOOM
Camera Interface	RJ45	RS485, RS232
Comunication Port	RS485 / PC RS232	
Transmit Speed	1400bps, 4800bps, 9600bps, 19200bps	1200~19200bps
Communication Distance	1.2KM	
Preset Position	128	
Cruising Track	6	
Alarm Sound	N/A	Yes
Matrix Setup	N/A	Yes
Dimensions	205(W) x 95(H) x 205(D) mm	206(W)x196(H)x90(D) mm
Operation Temperature	-10° C ~ 50° C	-10° C ~ +45° C
Operation Humidity	RH85% or less	
Storage Temperature	-10° C ~ 50° C	
Weight	1.2kg	1kg

