



PVC FLAME-RESISTING WIRE DUCT SERIES



GANG FENG Combustion PVC Trunking Series

Key Specifications/Special Features:

- 1.High insulation, anti-current puncture strength
- 2.Resist compression and impact
- 3.High oxygen value, good combustion resistance, self extinguishing
- 4.44 models for your choice

型号 Model	标准规格(mm×mm) Size	壁厚公差(mm) Thickness Tolerance
GF16-1	Φ16	1.0 -0.1
GF16-2	Φ16	1.2 -0.1
GF16-3	Φ16	1.4 -0.1
GF20-1	Φ20	1.1 -0.1
GF20-2	Φ20	1.2 -0.1
GF20-3	Φ20	1.3 -0.1
GF20-4	Φ20	1.4 -0.1
GF20-5	Φ20	1.5 -0.1
GF20-6	Φ20	1.6 -0.1
GF20-7	Φ20	1.8 -0.1
GF20-8(405)	Φ20	1.8 -0.1
GF25-1	Φ25	1.2 -0.1
GF25-2	Φ25	1.3 -0.1
GF25-3	Φ25	1.4 -0.1
GF25-4	Φ25	1.5 -0.1
GF25-5	Φ25	1.6 -0.1
GF25-6	Φ25	1.7 -0.1
GF25-7	Φ25	1.8 -0.1
GF25-8	Φ25	1.9 -0.1
GF25-9(405)	Φ25	1.9 -0.1
GF32-1	Φ32	1.3 -0.1
GF32-2	Φ32	1.4 -0.1
GF32-3	Φ32	1.5 -0.1
GF32-4	Φ32	1.6 -0.1
GF32-5	Φ32	1.8 -0.1
GF32-6	Φ32	1.9 -0.1
GF32-7	Φ32	2.2 -0.1
GF32-8(405)	Φ32	2.2 -0.1
GF38-1	Φ38	1.3 -0.1
GF38-2	Φ38	1.6 -0.1
GF38-3	Φ38	1.8 -0.1
GF38-4	Φ38	2.0 -0.1
GF40-1	Φ40	1.3 -0.1
GF40-2	Φ40	1.6 -0.1
GF40-3	Φ40	1.8 -0.1
GF40-4	Φ40	2.0 -0.1
GF50-1	Φ50	1.6 -0.1
GF50-2	Φ50	1.8 -0.1
GF50-3	Φ50	2.0 -0.1
GF50-4	Φ50	2.3 -0.1
GF63-1	Φ63	1.8 -0.1
GF63-2	Φ63	2.0 -0.1
GF63-3	Φ63	2.3 -0.1
GF63-4	Φ63	2.6 -0.1