

LICE23



Features

Weatherproof IR Camera

SONY/SHARP Color CCD

IR LED: ϕ 5X23PCS ,IR Distance:20M

Water Resistance : IP66

Auto White Balance(AWB)

Lens: Board Lens 3.6mm/F2.0(Optional)/td>

Dimension : 126(W) x 69(H) x 67(D)mm



Specifications

Model	LICE23SH	LICE23S	LICE23SF	LICE23H	LICE23HF
Image Sensor	1/3"SONY		1/4"SONY	1/3"SHARP	1/4"SHARP
Horizontal Resolution	480 TV Line		420 TV Line		
Pixels	PAL:752(H)×582(V) NTSC:768(H)×494(V)		PAL:500(H)×582(V) NTSC:510(H)×492(V)		
TV System	PAL/NTSC				
IR LED	ϕ 5 X 23 PCS				
IR Series Distance	20 M				
Lens	Board Lens 3.6mm/F2.0(Optional)				
Sync System	Internal				
IR Status	Under 10 Lux By CDS				
Usable Illumination	0 Lux/F2.0 (LED ON)				
IR Power On	CDS Auto Control				
S/N Ratio	≥48dB (AGC OFF)				
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75Ω)				
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec				
Operation Temperature	-10℃ ~ +50℃ RH95% Max				
Storage Temperature	-20℃ ~ +60℃ RH95% Max				
White Balance	Auto				
Power Source	DC12V 300mA				
Dimension	126(W) x 69(H) x 67(D)mm				
Weight	700g				