




FULLY NYLON INSULATED FEMALE & MALE DISCONNECTOR




INSULATED PART MATERIAL: NYLON
METAL PART MATERIAL: BRASS

WIRE RANGE A..W.G./mm ²	PRODUCT CODE	MATES WITH FEMALE & MALE	DIMENSION (mm)				
		WIDTH X THICKNESS	W	L	B	D	DRAWING
22-16 A.W.G. 0.5-1.5mm ²	FDFN1-250	.032 X .250 (0.8 X 6.35)	6.6	22.0	11.0	4.0	1
	MDFN1-250		6.4	23.0			2
16-14 A.W.G. 1.5-2.5mm ²	FDFN2-250	.032 X .250 (0.8 X 6.35)	6.6	22.0	11.0	4.5	1
	MDFN2-250		6.4	24.0			2
12-10A.W.G. 4-6mm ⁴	FDFN5-250	.032 X .250 (0.8 X 6.35)	6.6	24.0	13.0	6.3	1
	MDFN5-250		6.4	25.0			2



FULLY NYLON INSULATED FEMALE & MALE DISCONNECTOR



INSULATED PART MATERIAL: NYLON
METAL PART MATERIAL: BRASS

WIRE RANGE A..W.G./mm ²	PRODUCT CODE	MATES WITH FEMALE & MALE	DIMENSION (mm)				
		WIDTH X THICKNESS	W	L	B	D	DRAWING
22-16 A.W.G. 0.5-1.5mm ²	FDFNY1-250	.032 X .250 (0.8 X 6.35)	6.6	22.5	12.0	4.0	1
	MDFNY1-250		6.4	24.5	11.0		2
16-14 A.W.G. 1.5-2.5mm ²	FDFNY2-250	.032 X .250 (0.8 X 6.35)	6.6	23.0	12.0	4.5	1
	MDFNY2-250		6.4	24.5	11.0		2
12-10A.W.G. 4-6mm ⁴	FDFNY5-250	.032 X .250 (0.8 X 6.35)	6.6	23.0	12.0	5.0	1
	MDFNY5-250		6.4	24.5	11.0		2