



Model:		GSM-188B V20	Part No. :		Features		
Description:		Wireless Fixed Terminal+GPRS Function				<ol style="list-style-type: none"> Support 850/1900 and GSM900/1800 MHz optional Data Service, GPRS, Connect to a computer by USB port optional Rapid-dial number digit & CID setting Call restriction Reverse metering signal DTMF CLIP Lock up function: SIM card, Phone Available for being connected to the PBX as a wireless trunk Support to select whether or not send my caller identity Support Auto Dial out Wait Time ABS body housing (both top and bottom) Wall mountable External Omni directional Antenna with cable 	
							
Technical Parameter							
Operating Requirements							
1 Colors:		Opional					
2 Net Weight (Kg):		0.561 without battery					
3 Gross Weight (Kg)		0.713 without battery					
4 Piece by Carton:		10					
5 Product Size(mm)		219*160*41					
6 Packing Size (mm)		228* 264 *44					
Price Info.							
1. PSTN access is optional							
<ol style="list-style-type: none"> Antenna: osculum antenna and normal antenna optional, Osculum antenna: 3m cable Normal antenna: size 210mm 							

FXS	RJ-11*2		Antenna interface
USB interface	USB		Power supply interface
FOB	Hongkong		MOQ

Technology Parameter

- 1 Operating Freq.:GSM850/1900 MHz automatically switch
- 2 Power output: Max 2W(900MHz)/Maz 1W(1800MHz)
- 3 Channel interval:200KHz
- 4 Receive sensitivity:<-100dBm
- 5 Freq. error:<=0.1ppm

Model:		GSM-188B V31	Part No. :		Features			
Description:		Wireless Fixed Terminal+PSTN				<ol style="list-style-type: none"> Support GSM900/1800 and 850/1900 MHz optional Data Service, GPRS, Connect to a computer by USB port <p>Connection with GSM and PSTN network, the dialed number will call out through the GSM or PSTN network basing on the prefixes of call number. The GSM number will call out through GSM, otherwise other numbers will call out through PSTN. The extortionate bills for the PSTN-GSM connection are avoided and realize the LCR(least cost router) function</p> <ol style="list-style-type: none"> Rapid-dial for one pre-configured call number Call restriction Reverse metering signal and 12KHz and 16KHz selectable DTMF CLIP Call in / Call out / Call waiting limitation function Lock up function: SIM card, network, cell and operated company Local No. / direct No. / limited No. setting Available for being connected to the PBX as a wireless trunk Support to select whether or not send my caller identity Support three party conference(2 internal user and one outer) 		
								
1	Colors:	Opional				Technical Parameter		
2	Net Weight (Kg):	0.561 without battery				Operating Requirements		
3	Gross Weight (Kg)	0.713 without battery				1 Enviroment temperature:-10° C ---+40° C		
4	Piece by Carton:	10				2 Enviroment noise: below 60dB(A)		
5	Product Size(mm)	219*160*41				3 Relative humidity:45%~95%		
6	Packing Size (mm)	228* 264 *44				4 Atmosphere pressure:86~106KPa		
Price Info.							5 AC power voltage:100~380V, Freq. :50Hz	
1. Two freq. without GPRS/ USB port/ accessory battery, with normal antenna: \$43							6 Phone: DC 12V 1500mA	

- 2. Increase GPS: add \$2;
- 3. Increase USB port: add \$1.5 ;
- 4. Increase accessory battery: add \$3;
- 5. Increase 3m osculum antenna: add \$ 1.5
- 6. Increase 2 freq. : become 4 freq. optional, add \$2

FXS	RJ-11*1		FXO(for PSTN)	RJ-11*1
USB interface	1		Antenna interface	1
Power supply interface	1			
FOB	Hongkong		MOQ	3K

- 7 Battery: 1,2V 1300mAH Ni-MH rechargeable battery(accessory)
With battery: standby time: 72h, calling time: 4h
- 8 Antenna: osculum antenna and normal antenna optional,
Osculum antenna: 3m cable
Normal antenna: size 210mm

Technology Parameter

- 1 Operating Freq.:900/1800MHz automatically switch
- 2 Power output: Max 2W(900MHz)/Maz 1W(1800MHz)
- 3 Channel interval:200KHz
- 4 Receive sensitivity:<-100dBm
- 5 Freq. error:<=0.1ppm