

LIR30



Features

Weatherproof IR Camera

SONY/SHARP Color CCD

IR LED: ϕ 5X30PCS ,IR Distance: 25M

Water Resistance : IP66

Auto White Balance(AWB)

Lens: Board Lens 6mm/F2.0(Optional)

Dimension : 135(W) x 88(H) x 65(D)mm



Specifications

Model	LIR30SH	LIR30S	LIR30SF	LIR30H>	LIR30HF
Image Sensor	1/3"SONY	1/3"SONY	1/4"SONY	1/3"SHARP	1/4"SHARP
Horizontal Resolution	480 TV Line	420 TV Line			
Pixels	PAL:752(H)×582(V) NTSC:768(H)×494(V)	PAL:500(H)×582(V) NTSC:510(H)×492(V)			
TV System	PAL/NTSC				
IR LED	ϕ 5 X 30 PCS				
IR Series Distance	25 M				
Lens	Board Lens 6mm/F2.0(Optional)				
Sync System	Internal				
IR Status	Under 10 Lux By CDS				
Usable >Illumination	0 Lux/F2.0 (LED ON)				
IR Power On	CDS Auto Control				
S/N Ratio	≥48dB (AGC OFF)				
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75Ω)				
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec				
Operation Temperature	-10℃ ~ +50℃ RH95% Max				
Storage Temperature	-20℃ ~ +60℃ RH95% Max				
White Balance	Auto				
Power Source	DC12V 300mA				
Dimension	135(W) x 88(H) x 65(D)mm				
Weight	750g				