

ZT-MCTR TYPE T.C.T HOLE SAW

Model:SMI- ZT-MCTR-T.C.T-100



Specification:

▲Hollow Hole Saws

- 1.Usage:suitable for installing air conditions,water pipes,rainspouts,and etc
- 2.Surface treatment:Sand blasted,Blackoxide,Ti Coated,Metal shiny,etc

▲HSS Hole Saws

- 1.Special Feature:thebiggest cutting depth is 1.6mm
- 2.Surface treatment:NI Coated,Golden Finish,Metal shiny,Co Coated and etc

▲TCT Hole Saws

- 1.Special Feature:thebiggest cutting depth is 25mm
- 2.Surface treatment:Sand blasted,PEC and etc

▲Core Hole Saws

- 1.Special Feature:thebiggest cutting depth is 20mm
- 2.Surface treatment:Ni Coated and etc

▲Screwdrivers

- 1.Material:9CrSi,45#,Stwo
2. Usage:suitable for tightening and loosing filatures



Part No.	Φ		OVER RAU LENGTH	SHANK DIA
	METRIC	INCH		
HJ-DC1014	14	9/16 "	80	4
HJ-DC1016	16	5/8 "	80	4
HJ-DC1019	19	3/4 "	80	4
HJ-DC1022	22	7/8 "	80	6
HJ-DC1025	25	1 "	80	6
HJ-DC1028	28	1-1/8 "	80	6
HJ-DC1032	32	1-1/4 "	80	9
HJ-DC1035	35	1-3/8 "	80	9
HJ-DC1038	38	1-1/2 "	80	9
HJ-DC1048	48	1-7/8 "	80	9
HJ-DC1055	55	2-1/8 "	80	12
HJ-DC1060	60	2-3/8 "	80	12
HJ-DC1065	65	2-9/16 "	80	12
HJ-DC1070	70	2-3/4 "	80	12
HJ-DC1075	75	2-7/8 "	80	12
HJ-DC1080	80	3-1/8 "	80	12