

Outdoor High Speed Dome Camera (Economy)

SE506E



Feature: Die-Cast aluminum construction, Double Dome Housing, heater blower equipped, IP66 OSD, privacy mask (refer to camera table),256 Camera ID address
360° continuous pan, 90°tilt, 180°flip, 4 cruising tracks, 16 presets each track, 128 presets totally, shuttle scan RS485 communication, multi-protocol, 24VAC powered

Model	SE506E-27x	SE506E-30x	SE506-480	SE506E-980	SE506E-1000	SE506E-26X	SE506E-22X	SE506E-200
Image Sensor	1/4 Sony Super HAD							
Total Pixels	795x596	811x508	795x596	795x596	795x596	795x596	795x596	795x596
Synchronization	Internal							
Video Out	1.0Vp-p (75 OM, composite)							
White Balance	5 steps Auto/ Push auto/ Outdoor/ Indoor/ Special							
Scanning frequency	Horizon: 15.625k HZ , Vertic: 50 HZ							
Horizontal resolution	480TVL	480TVL	480TVL	480TVL	480TVL	480TVL	480TVL	470TVL
S/N Ratio	>48dB	>48dB	>50dB	>50dB	>50dB	>48dB	>48dB	>48dB
Electric Shutter (S)	1/50-10000	1/50-10000	1-1/10000	1-1/10000	1-1/10000	1/50-10000	1/50-10000	1/50-10000
Min. Illumination	0.001Lux	0.001Lux	0.01Lux	0.01Lux	0.01Lux	0.01Lux	0.001Lux	0.1Lux
BLC	9 Zones	9 Zones	9 Zones	9 Zones	9 Zones	Auto	Auto	Auto
Focal Length	f3.6-97.2mm	f3.3-99mm	f4.1-73.8mm	f3.5-91mm	f3.4-122.4mm	f3.5-91	f3.9-85.8	f3.9-85.8
Max. Zoom	270X	300X	216X	312X	432X	260X	220X	352X
Camera OSD	ON/OFF	ON/OFF	NO	NO	NO	ON/OFF	ON/OFF	ON/OFF
Gain	Auto/Manu							
Pan preset speed	300°/S							
Tilt preset speed	120°/S							
Pan speed	300°/S							
Tilt speed	120°/S							
Pan range	360° continuously endless							
Tilt range	90°, 180° auto flip							
Preset &. Track	128 presets, 6 tracks							
Communication	RS485, Cat5 cable, Multi-protocol supported							
Privacy Masking	NO	NO	YES	YES	YES	NO	NO	NO
WDR	NO	NO	YES	YES	YES	NO	NO	NO
DSS &. SensUp	YES	YES	NO	NO	NO	NO	YES	NO
Working Environment	negative 35 to 50 ; humidity 95% without agglomeration							
Weight &. Power	5Kg; 24VAC, 20VA							

