

LCDMIR23



Features

Plastic IR Dome Camera

SONY/SHARP Color CCD

IR LED: ϕ 5X23PCS ,IR Distance: 20M

Back Light Compensation(BLC)

Auto White Balance(AWB)

Lens: Board Lens 3.6mm/F2.0(Optional)

Dimension : ϕ 118 x 75(H) mm



Specifications

Model	LCDMIR23SH	LCDMIR23S	LCDMIR23SF	LCDMIR23H	LCDMIR23HF
Image Sensor	1/3"SONY	1/3"SONY	1/4"SONY	1/3"SHARP	1/4"SHARP
Horizontal Resolution	480 TV Line	420 TV Line			
Pixels	PAL:752(H) \times 582(V) NTSC:768(H) \times 494(V)	PAL:500(H) \times 582(V) NTSC:510(H) \times 492(V)			
TV System	PAL/NTSC				
IR LED	ϕ 5 X 23 PCS				
IR Series Distance	20 M				
Lens	Board Lens 3.6mm/F2.0(Optional)				
Sync System	Internal				
IR Status	Under 10 Lux By CDS				
Usable Illumination	0 Lux/F2.0 (LED ON)				
IR Power On	CDS Auto Control				
S/N Ratio	\geq 48dB (AGC OFF)				
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75 Ω)				
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec				
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max				
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max				
White Balance	Auto				
Power Source	DC12V 250mA				
Dimension	ϕ 118 x 75(H) mm				
Weight	350g				