



SPEC:
 Housing: Nylon 46 UL94V-0 Grey
 Contact: Phosphor Bronze Tin-Plated
 Working Temperature: -25 85
 Voltage Rating: 50V AC DC
 Insulation Resistance: $\geq 500M\Omega$
 Contact Resistance: $\leq 0.05\Omega$
 Withstand Voltage: 500V AC/Minute
 Dual Contact

Pin	A	B	C	Pin	A	B	C
4	3	51	6	24	23	251	25
5	4	61	7	25	24	261	27
6	5	71	8	26	25	271	28
7	6	81	9	27	26	281	29
8	7	91	10	28	27	291	30
9	8	101	11	29	28	301	31
10	9	111	12	30	29	311	32
11	10	121	13	31	30	321	33
12	11	131	14	32	31	331	34
13	12	141	15	33	32	341	35
14	13	151	16	34	33	351	36
15	14	161	17	35	34	361	37
16	15	171	18	36	35	371	38
17	16	181	19	37	36	381	39
18	17	191	20	38	37	391	40
19	18	201	21	39	38	401	41
20	19	211	22	40	39	411	42
21	20	221	23				
22	21	231	24				
23	22	241	25				

Order Information:
AC2.3 -1.0 -nP -S H
 Pitch No. of pole SMT Horizontal Type (Side entry)

TOLERANCE	
X: ± 0.50	X: $\pm 2^\circ$
X: ± 0.30	
XX: ± 0.10	

Access Electronic Co.,Ltd

PROJECTION	
UNITS	mm
SHEET SIZE	A4

SERIES	AC2.3-1.0-nP-SH
--------	------------------------