

VIP600 IP Videophone



Specifications and Features:

Standard and Protocol Support Communication: ITU-T H. 323V4

Video codec: ITU-T H. 263/H. 263+/H. 263++

Audio codec: ITU-T G. 711/G. 729/G. 723. 1A

Network protocols: TCP/IP, DHCP, Telnet, DNS, PPPoE, RTP, NAT, UDP, RTP, RTCP, TFTP

Bandwidth Support: 16kbps--512kbps

Network interface: 10/100Base-T, 2×RJ-45

P S T N: 1xRJ11

Video input: CVBS PAL/NTSC(RCA)

Video output: CVBS PAL/NTSC(RCA)

Audio input: Line(RCA)

Audio output: Line(RCA)

Video Quality

Video Resolution : QCIP (176×144) / CIF (352×288)

Video frame rate: Maximum CIF 30FPS

Use of video intensifying technology

User of pre/post image processing technology

Voice Quality

Voice Active Detect (VAD)

Comfort Noise Generation (CNG)

Adaptive Jitter Buffer

Hand free

* CCD Camera

Number of pixels: 300K pixels

* LCD Display

Type: Active TFT color LCD

Dimension: 5"

* User Interface

Display and input Language: Chinese and English

* Operating Environment

Temperature: 0~45

Relative humidity: 10%~90%

* Power Source

Input Voltage : 100~240V AC

Frequency: 50/60Hz

Power consumption: 18W

* Physical Dimension

Dimensions: 235mm (d) × 200mm (w) × 195mm (h)

Weight: 1.1kg

ZHEREN A-Z Traffic Plan:

Pre-pay calling plan: Total free for the Point to Point to all the VoIP devices published by LOOKIT. Call other location A-Z traffic at very good price. For example: USA, UK, Hong Kong \$0.02/m; China: \$0.019/m; Taiwan: China: \$0.027/m.

Virtual phone number (DID): Provide more than 50 countries local phone number bundled our VoIP device. User can choose its own geographical phone number to receive calls totally free! It also supports Transfer, Three parties calling, voice mail service etc.

Balance Check: User can check the consumption cost and called number etc. through our platform. Rechargeable the SIP phone is easy.