



TAHO

www.chintaho.com.tw

Multifunctional Next door monitor

Model No.: WT-2904-1



Function..

- Great feature is the multifunction: 1, next door wiretap.2, wireless next door wiretap.3, wireless spot wiretap.
- 3 phase audio frequency selectable: A(200Hz),B(800Hz),C(1200Hz)
- Metal detector head sensitivity: 20uV. Enclosed with the sticker which can be fixed on the wall or door.
- It can penetrate Concrete wall, reinforcing steel bar, and wood, Metal, Glass, and Brick. The audio can be magnified max 50000 times.
- It can be regarded as wireless spot monitor, effective distance 800m
- Because of the UHF347MHz ~ 353MHz steady transmission, the voice is superb fine.
- Separate recorder interface, so monitor and recorder can be working at the same time
- No need external power supply, superb compact. Easy for taking anywhere as you like. No installation trouble.
- Different from the traditional next door wiretap which user and device have to close the door. This unit can be used to monitor movable.

Function guide..



Will you have to monitor on the next door? No, if use WT-2904-1, you can monitor far from 800m.



It can filtrate other noise, only human-beings voice is clearer.



Can be regarded as wireless spot monitor, effective distance 800m.



Compact receiver is easy for taking anywhere.

Complete set..

	
Mainframe x1	Receiver x1
	
Earphone x2	Antenna x2
	
Detector x1	Manual x1

Specification..

wireless next door wiretap	
Frequency	347MHz ~ 353MHz
Shaking mode	Crystal Controlled
Adjustable breadth	NFM + / - 7KHz
Power consumption	10mA
Battery	AAAX2
Audio frequency	A(200Hz)B(800Hz)C(1200Hz)
Metal detector head sensitive	20uV
Microphone sensitivity	-110db
Audio magnified	50000 times
Penetration for metal detector head	can penetrate Concrete wall, reinforcing steel bar ,wood, Metal, Glass, Brick
Transmitting distance	800m (adopt wireless spot surveillance mode)
Penetration	8 floors(adopt wireless spot surveillance mode)
Surveillance mode	surveillance on next door.2,wireless spot surveillance
Recording mode	external recorder
Net weight	30g
Operating temperature	-20°C ~ 50°C
Weight	140g
Dimension	84*62*21 mm
Receiver	
Power consumption	10mA
Battery	AAAX2
Receiving frequency	173~175MHz
Shaking mode	Crystal Controlled
Adjustable breadth	NFM + / - 7KHz
Audio output	0.5W built-in loudspeaker and earphone jack
3 sects switch	1,power switch 2,silent receiving 3,standard receiving
Antenna	soft material length 18CM
Recording mode	external recorder
Operating temperature	-20°C ~ 50°C
Weight	140g
Dimension	84*62*21 mm