SL M92 | Product Specifications



■For long years, we provide products with fine design, superior quality, solid performance and non-malfuction durability. This particular item also enjoys a reputation for its compact size, minimal noise, energy efficiency and executing precision; which leads to its wide use as an ideal nuclear component for rolling service doors of both commercial and residential application.

SHINILION 湘联 科技

SL M92Characteristics

Model	SS92-140/12	SM92-140/12	SS92-180/12	SM92-180/12	SS92-230/12	SM592-230/12	SS92-300/6	SM92-300/6
Voltage(V)	220/230V 110/120V 50/60HZ							
Current(A)	2.6/4.5	2.6/4.5	2.7/5	2.7/5	3/5.2	3/5.2	2.8/5	2.8/5
Power(W)	540/490	540/490	570/530	570/530	630/570	630/570	580/530	580/530
Nominal speed(rpm)	12	12	12	12	12	12	6	6
Nominal torque(N.m)	140	140	180	180	230	230	300	300
Work time(min)	4	4	4	4	4	4	4	4
DBA(db)	< 58	< 58	< 58	< 58	< 58	< 58	< 58	< 58
Insulation level	B	B	B	B	B	B	B	B
Protection	Ip44	Ip44	Ip44	Ip44	Ip44	Ip44	Ip44	Ip44
Tube diameter(mm)	92	92	92	92	92	92	92	92
Overall size(mm)	Φ92 × 540	Φ92 × 570	Φ92 × 540	Φ92 × 570	Φ92 × 540	Φ92 × 570	Φ92 × 610	Φ92 × 640
Weight(kg)	12.6	13.5	12.6	13.5	12.6	13.5	15	15.9
Carton size	600 × 250 × 170	600 × 250 × 170	600 × 250 × 170	600 × 120 × 170	600 × 250 × 170	600 × 250 × 170	600 × 250 × 170	600 × 250 × 170
CTNS	625 × 270 × 370	625 × 270 × 370	625 × 270 × 370	625 × 270 × 370	625 × 270 × 370	625 × 270 × 370	625 × 270 × 370	625 × 270 × 370