

商业照明灯具系列

Commercial lighting fixture series

SD404 \varnothing 146 H100 \curvearrowright 130



AC: 220~230V 50Hz

型号 Model	产品代码 Code	光源灯功率 Suitable for lamp	灯头 Base	PF \geq 0.85时线路电流 Circuit current at PF \geq 0.85 (A)	重量 Weight (kg)
HQBN-35L/SD404	2550202026	MH 35W	Rx7S	0.21	-
HQBN-70L/SD404	2550204028	MH 70W	Rx7S	0.41	-

SD408 \varnothing 230 H110 \curvearrowright 210



Rx7S MH70W/50W/35W
G12 MH70W/50W/35W

AC: 220~230V 50Hz

型号 Model	产品代码 Code	光源灯功率 Suitable for lamp	灯头 Base	PF \geq 0.85时线路电流 Circuit current at PF \geq 0.85 (A)	重量 Weight (kg)
HQBN-70L/SD408	2550204027	MH 70W	Rx7S	0.41	-
HQBN-150L/SD408	2550209026	MH 150W	Rx7S	0.88	-

材质及特性

- 铝合金高压压铸壳体，并经静电喷塑处理。
- 高纯铝反射器。
- 耐冲击平板钢化玻璃。
- 热镀锌金属支架。
- 一体化装置，安装方便。

适用场所

- 商业场所，展示厅，博物馆，候客厅等室内照明。

Material & Characteristic

- High pressure die-casting aluminum alloy shaped the body, spraying plastics surface by electrostatic method,
- High purity aluminum reflector,
- Slab tempered glass which can endure more impact power,
- Galvanized iron bracket
- Integrative device, it is convenient to install.

Applications

- Commercial location, exhibition halls, Museum waiting halls, etc. (Indoor lighting)

