

Model No: 8909AZ

	Item	Value
GENERAL	Transmission Frequency	ISM 2,400-2,483 MHz
	Transmission Power	10mW/CE; 2mW/FCC
	Operating Frequency	2414MHz; 2432MHz; 2450MHz; 2468MHz
	Unobstructed Effective Range	50m(Min.)
	Modulation Mode	FM
	Operating Temperature	-10 ~ +50(Degree C) / +14~ +122(Degree F)
	Operating Humidity	≤85%RH
CAMERA	Imaging Sensor Type	CMOS
	Picture Total Pixels	PAL: 720×480 Pixels; NTSC: 720×576 Pixels
	View Angle	PAL: 80°; NTSC: 80°
	Minimum Illumination	0Lux
	Night Vision Range	4m
	Consumption Current	130mA(Max.)
	Power Supply	DC +12V or +24V
	Dimensions(W×D×H)	258*37*41 mm
	Weight	122g
	Operating Temperature	-20 ~ +50(Degree C) / -4~ +122(Degree F)
RECEIVER	LCD Screen Type	3.6 inches TFT-LCD
	Effective Pixels	960×240
	Receiving Sensitivity	≤-85dBm
	Video System	NTSC/PAL
	Color Configuration	R.G.B.delta
	Consumption Current	250mA(Max.)
	Power Supply	DC +12V or +24V
	Dimensions(W×D×H)	108*37*75 mm
Weight	165 g	